

1    **WHAT IS CLAIMED IS:**

2           1. A detachable folding clotheshorse comprising:

3           a seat with a top side, a bottom side and an outer periphery, the seat  
4    having a plurality of slots defined through the seat from the top side to the  
5    bottom, and each slot having a notch defined at the outer periphery, a supporting  
6    edge formed beneath the notch, and at least one protrusion formed at an inner  
7    wall of the slot adjacent the notch; and

8           a plurality of arms respectively and pivotally mounted in the slots, each  
9    arm having at least one channel longitudinally defined at a side facing the at least  
10   one protrusion for receiving the protrusion and at least one opening defined at a  
11   top-rear end of the channel for access of the protrusion to the channel.

12          2. The detachable folding clotheshorse as claimed in claim 1, wherein  
13   the slot has two protrusions respectively formed at two opposed inner walls  
14   adjacent the notch, and the arm has two channels defined at two opposed sides  
15   and two openings defined at the top-rear ends of the respective channels.

16          3. The detachable folding clotheshorse as claimed in claim 1, wherein  
17   the arm has a stop formed at a middle portion of the at least one channel.

18          4. The detachable folding clotheshorse as claimed in claim 3, wherein  
19   the arm has two clips formed at a top side of the arm and respectively at a front  
20   end and a rear end of the arm.

21          5. The detachable folding clotheshorse as claimed in claim 3, wherein  
22   the arm has a ring formed at a front end of the arm.

23          6. The detachable folding clotheshorse as claimed in claim 3, wherein  
24   the seat is secured on a tube, and the tube has an adjusting connector provided at

1 a lower end of the tube.

2 7. The detachable folding clotheshorse as claimed in claim 3, wherein  
3 the seat has a semi-circular cross section, and the slots are separately defined and  
4 arranged along radial direction of the seat.